

### **GT-H**

The most powerful strapping solution with maximum tension, suitable for **heavy-duty** applications in the metal, timber and construction Industries.

#### **GT-SERIES KEY FEATURES**

- » Simple and user-friendly interface
- to 25mm)

#### **SPECIFICATIONS**

**Package type**: Flat surface (min. 120 mm) Round surface (min. diam. 700 mm) Strap quality: PET Strap Width: 19 mm / 25 mm Strap thickness: from 0.8 mm up to 1.30 mm with 19 mm from 0.8 mm up to 1.05 mm with 25 mm Max. tension on single strap: 4.500 N **Soft mode**: 500 N Max. tension on the package: 9.000 N Max. Tension speed: 15,0 mt/min Joint type: Friction weld seal Weight: 4 Kg. (inc. battery) Battery: Akku Power SP5 18 Vdc 5.0 Ah Li-Ion

#### **OPTIONALS**

Akku Power SP5 Battery 18 Vdc - 5.0 Ah Li-Ion Battery charger for Li-Ion Battery Akku Power

#### **KEY FEATURES**

- » 4 setting mode available

### **POWER IN YOUR HANDS**







- - » Low maintenance required due to
- » Suitable for different strap sizes (from 9 mm » Tool status easy to check via computer





## **GT-Series**

**BATTERY STRAPPING TOOLS** FOR PLASTIC STRAPS



**STRAPPING** 



# **GT-Series**

PERFECTION IN EVERY DETAIL

**GT-Series** is the battery strapping tool range **by SIAT Maillis** that provides you the **optimized solution for all Industry applications, from light bundle strapping up to heavy duty pallet strapping.** 

#### STRAPPING IS MEANING-LESS WITHOUT ABSOLUTE PARAMETER CONTROL

Ranging from soft strap applications heavy duty automatic one, the **GT-Series** strapping tools is the optimized solution.

Easy to use and to adjust, the series ensures high and consistent levels of load security.

#### **SPECIFICATIONS**

Package type: Flat surface (min. 120 mm)<br/>Round surface (min. diam. 700 mm)Strap quality: PP/PETStrap Width: 9 mm / 16 mmStrap thickness: from 0.4 mm up to 0.85 mmMax. tension on single strap: 1.800 NMax. tension on the package: 3.600 NMax. Tension speed: 14,0 mt/minJoint type: Friction weld sealWeight: 3.5 Kg. (inc. battery)Battery: Akku Power SP114.4 Vdc 3 Ah Li-Ion

### **OPTIONALS**

Akku Power SP1 Battery 14.4 Vdc - 3.0 Ah Li-Ion Battery charger for Li-Ion Battery Akku Power

#### SIAT AND MAILLIS GROUP

SIAT is the famous Italian Brand of strapping hand tools, s/a wrappers and case handling machines, which forms part of the **Maillis Group**.

With **over 50 years experience**, Maillis is an essential player in Transit Packaging Solutions, designing and manufacturing complete wrapping, strapping and carton sealing systems.

Operating **5 production units around the world** and

employing over **1,200 qualified employees**, Maillis provides you with **reliable system solutions**, incorporating **machines**, **consumables and services** to face your everyday challenges across different industries.

Thanks to the state-of-the-art production equipment, optimized processes, premium raw materials and advanced technical know-how, we are able to **cover a wide range of applications** with unique material properties and **optimized solutions**.







#### **GT-Series. DISCOVER THE TECHNOLOGY**

## **GT-SMART**

Your access to the world of mobile strapping specifically designed by SIAT Maillis to outperform when used in **light applications, from bundle strapping up to light pallet strapping.** 



### **GT-ONE**

The perfect all-rounder for automatic strapping. It has been designed for **all medium pallet strapping applications.** 

#### **KEY FEATURES**

- » Weight: 3.5 Kg including battery (the lightest on the market)
- » Functioning mode: semi-automatic / manual / soft
- » Brushless moto
- » Perfect handling
- » Robust cover realized with HIGH TECH materials
- » Rubber non-slip handle
- » Front & rear guides adjustable for all strap dimensions

### **SPECIFICATIONS**

- Package type: Flat surface (min. 120 mm) Round surface (min. diam. 700 mm) Strap quality: PP/PET Strap Width: 10 mm / 16 mm Strap thickness: from 0.5 mm up to 1.10 mm Max. tension on single strap: 2.750 N Soft mode: 500 N Max. tension on the package: 5.000 N
- Max. tension on the package. 5.000
- Max. Tension speed: 15,0 mt/min
- Joint type: Friction weld seal Weight: 3.7 Kg. (inc. battery)
- Battery: Akku Power SP3 14.4 Vdc 4.0 Ah Li-Ion

#### **OPTIONALS**

Akku Power SP3 Battery 14.4 Vdc - 4.0 Ah Li-Ion Battery charger for Li-Ion Battery Akku Power

#### **KEY FEATURES**

- » Maximum tension: 2750 Newton
- » Weight: 3,7 Kgs including battery
- » 4 setting mode available
- » Battery: Akku Power SP3 14.4 Vdc 4.0 Ah Li-Ion
- » Perfect handling
- » Robust cover realized with HIGH TECH materials
- » Rubber non-slip handle
- » Front & rear guides adjustable for all strap dimensions

