

POLYESTER STRAPPING

Range and Technical Specification

Tensium® Polyester Strapping

Tensium® polyester strapping is available in smooth or embossed finish, in black and green as standard and a range of widths. Bespoke colours are available subject to a minimum order quantity. A full range of straps suitable for friction weld tools and standard mechanical tools and all types of strapping machines available on the market today.

Description	Quality	Surface	Width (mm)	Thickness (mm)	Breakload		Length (m/coil)
					(kgf)	(N)	
Tensium 9530	Standard	Embossed	9,5	0,60	250	2450	3000
Tensium 9734	Standard	Embossed	9,7	0,57	225	2210	3400
Tensium 1226	Standard	Embossed	11,9	0,57	270	2650	2600
Tensium 2525	Standard	Embossed	12,5	0,50	260	2550	2500
Tensium 2565	Standard	Embossed	12,5	0,60	320	3140	2500
Tensium 2520	Standard	Embossed	12,5	0,68	380	3730	2000
Tensium 1517	Standard	Embossed	15	0,67	395	3875	1700
Tensium 5506	Standard	Embossed	15,5	0,60	400	3925	1800
Tensium 5518	Standard	Embossed	15,5	0,70	420	4120	1800
Tensium 5514	Standard	Embossed	15,5	0,76	520	5100	1400
Tensium 1612	Standard	Embossed	16	0,80	600	5890	1200
Tensium 1688	Standard	Embossed	16	0,88	620	6080	1200
Tensium 1610	Standard	Embossed	16	1,00	680	6670	1200
Tensium 1980	Standard	Embossed	19	0,80	700	6870	650
Tensium 1910	Standard	Embossed	19	1,00	820	8045	1000
Tensium 2518S	Standard	Smooth	12,4	0,86	420	4120	1800
Tensium 1612S	Standard	Smooth	16	0,88	650	6380	1200
Tensium 1613S	Standard	Smooth	16	1,00	700	6870	1220
Tensium 1910S	Standard	Smooth	19	1,00	900	8830	1000

Tensium® Plus Polyester Strapping

The M. J. Maillis product range also includes the Tensium® Plus quality, a high performance polyester strapping engineered from high quality raw material, ideal for medium to heavy-duty special strapping applications that combines the performance properties of both steel and plastic strapping. Its elongation and recovery characteristics help straps stay tight and absorb impacts without breaking.

Description	Quality	Surface	Width (mm)	Thickness (mm)	Breakload		Length (m/coil)
					(kgf)	(N)	
Tensium Plus 9238	Special Duty	Smooth	9,2	0,52	210	2060	3810
Tensium Plus 1132	Special Duty	Smooth	11,1	0,52	240	2355	3200
Tensium Plus 1128	Special Duty	Smooth	11,1	0,60	270	2650	2800
Tensium Plus 2519	Special Duty	Smooth	12,5	0,70	400	3925	1980
Tensium Plus 5514	Special Duty	Smooth	15,5	0,76	570	5590	1400
Tensium Plus 1688	Special Duty	Smooth	16	0,88	650	6375	1220
Tensium Plus 1613	Special Duty	Smooth	16	1,00	700	6865	1220
Tensium Plus 1975	Special Duty	Smooth	19	1,27	1050	10300	750

Unboxed Coils or shrink wrapped
 Colour: Green, Black. Other colours on request
 Core Size: 406 mm x 150mm
 Coils per pallet: 24 or 48
 Jumbo Coils are also available



www.maillis.com

Issue No 02 (05/06) English

All specifications are correct at time of print, are for guidance purposes only and subject to change without prior notice.

M.J. MAILLIS GROUP

M.J. MAILLIS GROUP
 5 XENIAS & HAR. TRIKOUPI STR, KIFISSIA, 145 62 ATHENS, GREECE
 TEL: +30 210 6285000 FAX: +30 210 8080301 EMAIL: info@maillis.gr

